



- Notes:
- 316 SS, 18-8 Fasteners, Plastics, and Elastomers
 - Weight: 5.07 lbs.
 - Nozzle Sizes: Range from 0.060" to 0.100"
 - Flow Range: 3 to 6 (US)GPM (11 to 23 lpm)
 - Pressure Range: 100 to 1000 PSIG (7 to 70 bar)
 - Min. Full Wash Cycle: 3 1/2 minutes.
 - Clearance: Tee Housing Section is designed to fit through a $\varnothing 50$ mm bung hole
 - Temperature: 180 °F (82 °C) Maximum

UNLESS OTHERWISE SPECIFIED
 * DIMENSIONS ARE IN INCHES
 * [] DIMENSIONS ARE mm
 * DEBURR ALL SURFACES
 * FILLET RAD.: 0.015
 * TOLERANCES:
 .XX ±0.01
 .XXX ±0.005
 ANGLE ±1°

MATERIAL:
 Material

FINISH (UNLESS OTHERWISE SPECIFIED):
 ??? Ra

SCALE: Full

GAMAJET CLEANING SYSTEMS, INC.

604 Jeffers Circle
 Exton, PA 19341-2524

TITLE	Cut Sheet	
EQUIPMENT	Gamajet HD-BB	
DWG. NO.	Gamajet HD-BB Cut Sheet	SHEET 1 OF 1

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

DRAWN	DATE	Rev.	Description
MQL	12/02/05	1	New Drawing
MQL	12/07/05	2	Modified Note & change drawing name
MQL	09/14/07	3	Change design to one peice
SAM	12/03/09	4	Added Body Dimensions